

Design by Helena Chmelíková

You can create various patterns on the tubes.





PRECIOSA Twin™ 117 01 323; 2 x 4 mm



Preciosa Ornela introduces beads and seed beads from the PRECIOSA Traditional Czech Beads™ brand.

Preciosa-Ornela.com



SEWN EARRINGS MADE FROM PRECIOSA TWIN**
Filled Tubes

PRECIOSA

Filled Tubes

Try using the smaller PRECIOSA Twin™ Pressed Beads to assemble earrings in a variety of patterns. You can make use of the wide range of finishes and shades on offer. We wish you pleasant hours spent beadworking.

Materials and tools:

PRECIOSA Twin™(T) 117 01 323; 2 x 4 mm; 53330/28101 green silver; 200x

PRECIOSA beads (**B**) 111 19 001 or 151 19 001; 10 mm; an associated shade; 6x

- a 0.20 mm nylon line; a thin needle; scissors; snipping pliers; needle nose pliers



- a 40 mm eye pin; an 18 mm eye pin; 4 mm rings; earring hooks



Difficulty:

Procedure:

Sew through the T carefully.

Step 1:

String 5x **T**. Tie them off. Thread the line through both holes in the **T** nearest to the knot.



Step 2:

Thread the line through the second holes in the T. Add 2x T into each gap. After connecting them all around, thread the line through both holes in the T.



Step 3: Thread the line through the second holes of the T. Add 1x T to each gap. After connecting them all around, thread the line through both holes at the T.



Step 4: Repeat Step 3 a total of 7 more times (so that you sew it a total of 8x).



Step 5: Reduce the **T**. Only string them into every second gap. Imitate the layout in Step 2. Do not tighten.



Step 6: Thread an eye pin through the tube. String 2x **B** onto it.







Step 7:

Also thread the line through the second holes of the T. Tighten. Thread it through several more holes one more time. Finish between the T in the body of the tube. Make sure that the eye pin does not fall out. Step 9: Sew the second earring.



Step 10: Link a **B** onto eye pins. Hang them from the eyes next to the tubes.





Step 11: Hang an earring hook on the second eye using a ring.





Step 8:

Shorten the eye pin. About 8 mm of wire should protrude above the tube. Grasp the wire between the points of the needle nose pliers. Twist it around the point. Gently tighten the eye "back" behind the **T**, so that it is located in the centre above the tube.



